

SEE HEAT SIGNATURES MORE THAN 1.5 MILES AWAY

FLIR's new Scout BTS-Series gives outdoor enthusiasts even more choices and control in their thermal viewing experience. Featuring a full coverage eyepiece, inter-ocular adjustment, straightforward controls, interchangeable quick disconnect lenses, and the unrivaled performance that only FLIR's high resolution thermal cores can deliver, the Scout Bi-Ocular is a must have for any avid outdoor enthusiast. Keep track of your party, see animals, track game, and travel safely at night or in conditions with poor visibility. Employing either a 320×240 or 640×480 FLIR thermal imaging core, the Scout Bi-Ocular allows you to see more and see farther than any other night vision technology.

KEY FEATURES OF THE SCOUT BTS-SERIES:

- Quick-Disconnect Modularity: Customize thermal capability for specific tasks by selecting from three available lens options 35mm, 65mm, or 100mm extended range.
- Extended Range Options: The BTS-X Pro provides excellent long-range viewing with sharp 320 x 240 native resolution and a 2x digital e-zoom step in 160 x 120 resolution. The BTS-XR Pro delivers even greater range performance by supplying crisp, clear 320 x 240 native resolution in the viewfinder AND in the 2x digital e-zoom mode, plus an additional 4x digital e-zoom step in 160 x 120. Full 640 x 480 resolution imagery in the BTS-XR Pro is accessible via the video jack.
- Enhanced Lens Surfaces: Raised rubber sleeves and captive low-profile lens caps help protect your lens investment as well as provide excellent grip/sensitivity.
- Faster Power & Battery Swap: A quick release hot-shoe literally makes access to AC power a "snap," and a latched battery door provides fast access for battery changes.
- One-Touch Recording: The ability to capture both photos and video is standard on all Scout Bi-Ocular models.

If you are serious about the great outdoors, why limit your opportunity to only the daylight hours? Experience nature in vivid detail 24/7 with the Scout BTS-Series.









www.SCOUTBASECAMP.ca 1.877.766.5412



BTS-Series Thermal Night Vision Camera



SPECIFICATIONS

Resolution

Size (L × W × H)

Weight (w/o lens)

System BTS-X Pro

 320×240

 640×480

11.0" x 6.5" x 2.63"

2.20 lbs

Operating / Storage Temp. -4°F - 140°F (-20°C - 60°C) / -40°F - 167°F (-40°C - 75°C)

IMAGE PRESENTATION

White Hot, Black Hot, InstAlert $^{\text{TM}}$

Viewfinder Video Output NTSC or PAL composite video

(9 Hz refesh rate)

320 x 240 NTSC or PAL 640 × 480 NTSC or PAL

FILE STORAGE/DATA TRANSFER

Still Image / Video Storage Yes SD/SDHC Card Enabled Yes

COMMON FEATURES

External Video (via RCA jack)

Startup 2 seconds

E-Zoom

4 AA Batteries; NiMH (included), Li-lon, or Alkaline Battery

Rating IP-67 (with lens attached only)

INCLUDED ACCESSORIES

BTS-X Pro/BTS-XR Pro

Hot Shoe Charging & Video Output Attachment, 4 Rechargeable AA NiMH Batteries, AC Power Adapter/Charger, Neck Lanyard, USB Cable, Video Output Cable, Hard Carrying Case, Product CD with Ops Manual, FLIR Video Player Software and End User Graphical User Interface (GUI)

LENSES (purchased separately)						3
Lens Options	QD35	QD65	QD100	QD35	QD65	QD100
Size	Ht 2.2" Dia - 3.1" Ø	Ht 3.3" Dia - 3.1" Ø	Ht 4.6" Dia - 3.1" Ø	Ht 2.2" Dia - 3.1" Ø	Ht 3.3" Dia - 3.1" Ø	Ht 4.6" Dia - 3.1" Ø
Field of View	13° × 10°	7° × 5°	5° × 3°	18° × 13°	10° × 8°	6° × 4°
E-Zoom FOV (H x V)						
2x	6.5° × 5° (160 x 120)	3.5° × 2.5° (160 x 120)	2.5° × 1.5° (160 x 120)	9° × 6.5° (320 x 240)	5° × 4° (320 × 240)	3° × 2° (320 × 240)
4x	N/A	N/A	N/A	4.25° × 3.25° (160 × 120)	2.5° × 2° (160 × 120)	1.5° × 1° (160 × 120)
RANGE PERFORMANCE*						
Detect Man	850 yds	1400 yds	2270 yds	1200 yds	2075 yds	2675 yds
Recognize Man	200 yds	400 yds	590 yds	305 yds	535 yds	710 yds

^{*}Actual range may vary depending on camera setup, environmental conditions, user experience, and display method.

FLIR Systems, Inc. CS World Headquarters

FLIR Systems, Inc. 70 Castilian Dr. Goleta, CA 93117

LISA

PH: + 1 877 773 3547 PH: + 1 805 964 9797 FX: + 1 805 685 2711 sales@flir.com

EUROPE CS Eurasian Headquarters

FLIR Systems CS BV Charles Petitweg 21 4847 NW Teteringen - Breda Netherlands PH: +31 (O) 765 79 41 94

FX: +31 (O) 765 79 41 99 flir@flir.com

FLIR Systems, Inc. Corporate Headquarters

FLIR Systems, Inc. 27700 SW Parkway Ave. Wilsonville, OR 97070 PH: + 1 877 773 3547 FX: + 1 503 498 3153

sales@flir.com

www.FLIR.com

Always consult federal, state, and local laws governing fishing, hunting, and shooting sports prior to the use of this thermal/infrared night vision camera to ensure full compliance with all appropriate regulations governing sportsman use. State and local laws vary, so regularly consult those specific to the region of use/activity of interest. Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. ©2012 FLIR Systems, Inc. Specifications are subject to change without notice. Visit flir.com for the most up-to-date specifications. O32812

